

Dektite® Solar 200 Kit

Specialty Flashing Solutions for Solar Pipes and Cables



Features

- **Everything you need to fix to tile or tin roofs including**
 - 2 X Red Silicone Dektites with a 25-35mm nipple rated at -50° C to 200° C constant temp
 - 1 X Flashing neutral cure engineering grade Silicone Adhesive rated at -50° C to 165° C
 - 16 X 10 Gauge 16mm class 3 roofing screws
- **No more messy installations**
- **High UV Resistance**
- **Versatile Flashing accommodates 25 - 35mm**
- **20 year warranty**
- **Bushfire Attack Level (BAL) 29**

Dektite® Premium

More flexible Sizing for Better Coverage



Ask us for the rest of the Dektite Range

Features

- **Low profile base with watershed sleeve**
Improves water run off and protects silicone sealant
- **Larger square base will cover a larger opening**
So more forgiving for penetration openings and allows for steeper roof pitch
- **Unique cone design**
Provides 10mm continuous contact with flashing pipe providing a watertight seal
- **Clear markings in metric and imperial measurements**
Makes for easier cutting to size
- **Size Range - Number 0-9**
Available in black and Grey EPDM and Red Silicone
- **Twenty year warranty**
Just fit and forget it
- **Bushfire Attack Level (BAL)**
Black EPDM Dektites are rated at BAL 12.5
Red Silicone Dektites are rated at BAL 29