

What's NEW



Photoelectric Smoke Alarms



AC220~240V 50 Hz

Two Great Models available
Key features in both Models

- Low Battery Warning
- Interconnectable
(up to 40 detectors)
- Hush Function



Photoelectric Smoke Alarms are more sensitive at detecting slow smouldering fires before they burst into flames. This makes them ideal for residential use.

There are two Models to choose from:

Model 1: The 3786PH14 Model includes a 9V Battery Backup. It's simple to change the battery every year with the Easy Install click-on Body & Base.

Model 2: The 3786PH14LI Model has a 10 Year Lithium Battery inside the unit. There's no need to ever change the battery – just replace the smoke alarm.

SmokeWatch – where safety is the priority

Model 1
with **9V**
Battery
Backup
Cat No:
3786PH14

Model 2
with **10 Year**
Lithium
Battery
Cat No:
3786PH14LI

SPECIFICATIONS (both Models)	
Alarm Volume:	Loud (greater than) 85dB audible alarm
Sensitivity:	0.10~0.16dB/m
Coverage:	20 to 40m ² capacity
Hush Time:	Approx 8 minutes
Operation Current:	<100mA
Temperature:	Operating Range +5° to +45° C
Humidity:	Relative 10% to 90%
Standards:	AS3786:2014 and ActivFire certified
Warranty:	Product Replacement Warranty only – 5 years limited (excludes battery)
Power:	Mains powered AC220~240V with 9V battery backup
3786PH14 Model only	
Battery Backup with a 9V Battery supplied	
Low Battery Warning Feature	
3786PH14LI Model only	
Lithium Battery inside unit with Pull Tab to activate	
Low Battery Warning Feature	

Date Released: August 2018



www.omegapower.com.au sales@omegapower.com.au
VIC (03) 8793 9700 NSW (02) 9734 9944 QLD (07) 3283 1199
SA (08) 8345 0017 WA (08) 9271 9787

